AD-753 089

FABRICATION OF TWENTY-TWO SOUNDING ROCKET VEHICLE SYSTEMS

George C. Alford, et al
Thiokol Chemical Corporation

Prepared for:

Air Force Cambridge Research Laboratories

September 1972

DISTRIBUTED BY:



National Technical Information Service U. S. DEPARTMENT OF COMMERCE 5285 Port Royal Road, Springfield Va. 22151



FABRICATION OF TWENTY-TWO

SOUNDING ROCKET VEHICLE SYSTEMS

George C. Alford David M. George Paul W. Hoekstra

Thiokol Chemical Corporation
Wasatch Division
P. O. Box 524
Brigham City, Utah 84302
Contract No. F19628-72-C-0166
Project No. 7659
Task No. 765904
Work Unit No.76590401

FINAL REPORT

Period Covered: February 18, 1972 through September 30, 1972


September 1972

Contract Monitor: Edward S. Mansfield
Aerospace Instrumentation Lab.

Approved for public release; distribution unlimited.

Prepared

for



Air Force Cambridge Research Laboratories
Air Force Systems Command
United States Air Force
Bedford, Massachusetts 01730

Security Classification

Security Classification			
DOCUMENT CONTROL DATA - R & D			
(Security classification of title, body of abstract and indexing a	nnotation must be e	ntered when the	overall report is classified)
1 ORIGINATING ACTIVITY (Corporate author)		28. REPORT SECURITY CLASSIFICATION	
THIOKOL CHEMICAL CORPORATION .		Unclassified	
WASATCH DIVISION, P. O. BOX 524		2b. GROUP	
BRIGHAM CITY, UTAH 84302			
3 REPORT TITLE		 	
FABRICATION OF TWENTY-TWO SOUNDING ROCKET V	VEHICLE SYSTI	ems	
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)			A
,		000	Approved
Scientific Final. 18 February 1972 - 30 s Author(5) (First name, middle initial, last name)	September J	.972	17 Oct 72
George C. Alford			
•			
David M. George			
Paul W. Hoekstra			
6 REPORT DATE	75. TOTAL NO. O	FPAGES	76, NO. OF REFS
SEPTEMBER, 1972	17		NONE
88. CONTRACT OR GRANT NO.	98. ORIG:NATOR'S REPORT NUMBER(5)		BER(5)
F19628-72-C-0166 ''			
ь рвојест, Task, Work Unit Nos.			
7459-04-01			
c. DoD Element 63404F	9b. OTHER REPORT NO(S) (Any other numbers that may be essigned this report)		
ه. DoD Subelement 63RKTS	AFCRL-72-0533		
10 DISTRIBUTION STATEMENT			
A - Approved for public release; distribut	ion unlimite	ed.	
11 SUPPLEMENTARY NOTES	12. SPONSORING	MILITARY ACTI	VITY
	AIR FORCE	CAMBRIDGE I	RES. LABORATORIES (LC)
	L. G. Hanso		, mar 1012 1012 1 1 - 1
TECH, OTHER.	Bedford, Ma		ts 01730
13. ABSTRACT	bearora, in	20040114000	01750
Twenty-two sounding locket systems were	prepared an	d delivere	d by Thiokol Chemical
		. 1	

Twenty-two sounding locket systems were prepared and delivered by Thiokol Chemical Corporation consisting of fourteen (14) Ute-Tomahawk vehicles and eight (8) Paiute-Tomahawk vehicles. In addition to fabrication, assembly and adjustment of vehicle components, Thiokol provided additional related support to Air Force Cambridge Research Laboratories (AFCRL) in the form of static tests and computational, analytical, and field engineering services.

Rocket motors and igniters; the TE-416 Tomahawk, the TU-715 Ute, and the TU-716 Paiute were major components of the twenty-two sounding rocket systems. Other system components included the Ute/Paiute tail assembly, launch lugs, Ute/Paiute-Tomahawk interstage adapter, Tomahawk tail assembly, and Tomahawk despin modules.

Four Paiute booster motors were statically fired to verify the propellant batch. The tests demonstrated operation over the temperature range -75° F to $+125^{\circ}$ F and confirmed satisfactory operation after vibration and shock tests. On the basis of these tests the operational temperature range has been established at -75° F to $+140^{\circ}$ F.

Computations and analyses were completed for Ute/Paiute-Tomahawk vehicles to allow theoretical prediction of trajectories, roll rate and pitch natural frequency histories, static stabilities, wind weighting data, and heating analyses.

Field engineering services were provided in support of the launch of a Paiute-Tomahawk vehicle from Eglin Air Force Base, Florida. In a near nominal flight a payload weighing 215 pounds was carried to an apogee of 227 kilometers.

DD FORM .. 1473

Unclassified
Security Classification KEY WORDS LINK B LINK C ROLE ROLE Sounding Rocket Rocket Motor Solid Propellant Tomahawk Paiute Ute

Ib

Unclassified
Security Classification

FABRICATION OF TWENTY-TWO

SOUNDING ROCKET VEHICLE SYSTEMS

George C. Alford David M. George Paul W. Hoekstra

Thickol Chemical Corporation Wasatch Division P. O. Box 524 Brigham City, Utah 84302

Contract No. F19628-72-C-0166 Project No. 7659 Task No. 765904 Work Unit No.76590401

FINAL REPORT

Period Covered: February 18, 1972 through September 30, 1972

September 1972

Contract Monitor: Edward S. Mansfield
Aerospace Instrumentation Lab.

Approved for public release; distribution unlimited.

Prepared

for

Air Force Cambridge Research Laboratories

Air Force Systems Command

United States Air Force

Bedford, Massachusetts 01730

II

Qualified requestors may obtain additional copies from the Defense Documentation Center. All others should apply to the National Technical Information Service.

FOREWORD

This final report is submitted to Air Force Cambridge Research Laboratories (AFCRL) by Thiokol Chemical Corporation in compliance with Contract No. F19628-72-C-0166.

The contract was issued by the Electronic Systems Division (PPR); Air Force Systems Command, USAF; Laurence G. Hanscom Field; Bedford, Massachusetts 01730. Mr. Edward S. Mansfield served as Contract Monitor.

Management of work conducted on this contract was handled by Thiokol Chemical Corporation, Wasatch Division, P. O. Box 524, Brigham City, Utah 84302. Fabrication of Ute and Paiute booster motors and Paiute static tests were performed at the Wasatch Plant near Brigham City, Utah, while Tomahawk motor fabrication was performed by the Elkton Division at Elkton, Maryland. The Astro-Met Plant of the Wasatch Division had primary management responsibility and performed hardware fabrication, analytical services, and field engineering support.

TABLE OF CONTENTS

Section	Description	Page
	ABSTRACT	ii
	FOREWORD	iii
I	INTRODUCTION	1
II.	FABRICATE AND STATIC FIRE FOUR PAIUTE MOTORS	2
III	FABRICATE UTE MOTORS	4
IV	FABRICATE PAIUTE MOTORS	5
V	FABRICATE TOMAHAWK MOTORS	6
VI	FABRICATE FLIGHT HARDWARE	7
VII	COMPUTATIONAL AND ANALYTICAL SERVICES	8
VIII	RELATED CONTRACTS	9
IX	CONTRIBUTING PERSONNEL	10
Х	PROGRAM RESULTS AND RECOMMENDATIONS	11

I INTRODUCTION

A program has been completed to provide twenty-two sounding rocket systems consisting of fourteen Ute-Tomahawk vehicles and eight Paiute-Tomahawk vehicles. Four additional Paiute booster motors were fabricated and statically fired to verify the batch of propellant used in all the boosters. Support was provided for computational, analytical and field engineering services.

This final report is presented in sections which describe the effort in each work area in more detail.

II FABRICATE AND STATIC FIRE FOUR PAIUTE MOTORS

Four TU-716, Paiute, booster motors designated serial numbers 003, 004, 005, and 006 were fabricated and fired in a static test stand to verify propellant characteristics and to confirm their capability to withstand environmental extremes. Static tests and pretest conditioning was in accordance with TWR-5750, "Test Requirements for Preproduction Testing of TU-716 Motors."

In the test sequence motor S/N 003 was subjected to vibration in a Board Course Test followed by Temperature Cycle Tests along with the other three motors. After temperature cycling, motor S/N 003 was subjected to shock in a Drop Test and subsequently static fired after conditioning at 60° F.

All four motors were subjected to the temperature cycles listed in Table I.

Post test analyses indicate the firing temperature range for the Paiute 17-716 motor can be extended to -75° F to $+140^{\circ}$ F. Storage temperature range has been demonstrated to be -75° F to $+175^{\circ}$ F.

All motors performed satisfactorily and met all test requirements.

TABLE I TEMPERATURE HISTORY FOR PAIUTE MOTORS $\mbox{S/N}$ 003, 004, 005, and 006 PRIOR TO STATIC TESTS

	TABLE I	
ጥ፫ ለ ከ ፫ D ለጣ!	IDV UTCTONV ECD DATUTE	. Momon c
	RE HISTORY FOR PAIUTE 05, and 006 PRIOR TO	
27.1. 000, 001, 0	os, and ood inton io	DIALLO LADID
Temperature (°F)	Motor S/N	Time (hours)
Ambient	All	Start
175 <u>+</u> 5	A11	48,25
-75 <u>+</u> 5	A11	48.16
175 ± 5	A11	48.00
~75 ± 5	A11	48.09
175 ± 5	A11	48.16
-75 <u>+</u> 5	A11	48.00
Ambient	006	163,00
Ambient	003, 004, and 005	162.00
60 <u>+</u> 5 *	003	52,50
60 <u>+</u> 5 *	004	51,50
125 <u>+</u> 5 *	005	48.38
-75 <u>+</u> 5 *	006	48.50
		10000

^{*} Motor was fired in less than .5 hour after removal from conditioning box at temperature indicated.

III FABRICATE UTE MOTORS

Fourteen TU-715, Ute, booster motors were fabricated including igniters, MXU/35A modified per Thiokol drawing number 7U44048-02. Motors and igniters were delivered to Eglin AFB, Florida.

是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人

IV FABRICATE PAIUTE MOTORS

Eight TU-716, Paiute, booster motors were fabricated including igniters, MXU/35A modified per Thiokol drawing number 7U44048-02. Motors and igniters were delivered to Eglin Air Force Base, Florida.

The trade of the contract of t

V FABRICATE TOMAHAWK MOTORS

Twenty-two TE-416, Tomahawk, rocket motors were fabricated including pyrogen-type igniters TE-P-415 per Thiokol drawing number E-19504-05 equipped with 18-second pyrotechnic ignition delays. Tomahawk motors were fabricated with tension joint head caps per Thiokol drawing E-15209-25. Motors and igniters were delivered to Eglin Air Force Base, Florida.

的现在分词,我们是是一个时间,他们是一个人,我们是是一个人,我们是一个人,我们就是一个人,我们们是一个人,我们们是一个人,我们们是一个人,我们们就会会会会会会

VI FABRICATE FLIGHT HARDWARE

Twenty-two sets of flight hardware for Ute/Paiute-Tomahawk two-stage sounding rocket vehicles were fabricated and delivered to Eglin Air Force Base, Florida. This fabrication effort included; purchasing raw material and components, machining and inspection of mechanical components, wiring and assembly of electrical components in the interstage adapter and despin, assembly of mechanical components including adjustment and survey of tail assembly fins to establish the desired effective incidence angle, and marking and packaging for shipment.

Flight hardware items delivered for these sounding rocket systems are listed in the following table. All items can be used interchangeably on Ute-Tomahawk or Paiute-Tomahawk vehicles.

TABLE II

FLIGHT HARDWARE FOR TWENTY-TWO UTE/PAIUTE-TOMAHAWK

SOUNDING ROCKET VEHICLES

Description	Drawing Numbers	Quantity
Interstage Adapter Assembly Ute/Paiute-Tomahawk	Assembly R-01814 including Interstage R-01640 (Rev. G)	22
Despin Module	Assembly R-01707-02 (Rev. C)	22
Ute/Paiute Tail Assembly	Assembly R-01665-02 (Rev. C)	22
Launch Lug Assembly Ajax-type for Ute/Paiute	Assembly R-J1824 including Lugs C-01667 and C-01653	22
Launch Lug Assemily, MRL-type for Ute/Paiute	Assembly R-01822 including Lugs C-01806 and C-01805	22
Tomahawk Tail Assembly	Assembly R-01660 (Rev. C)	22

VII COMPUTATIONAL AND ANALYTICAL SERVICES

Theoretical analyses, adjusted for data obtained in previous flights, and digital computer codes were used to compute performance parameters for Ute/Paiute-Tomahawk vehicles. The performance parameters will be useful in predicting flight conditions for the twenty-two vehicles delivered under the contract. Prediction of flight conditions include trajectories, roll rate and pitch natural frequency histories, static stabilities, wind weighting data, and heating analyses.

是是一种,我们是是一个人,我们是是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们就

In association with this task, field engineering support was provided at Eglin Air Force Base, Florida, for the flight of a Paiute-Tomahawk vehicle. Data from this flight indicated flight performance parameters were very near the pre-flight predictions. A payload weighing 215 pounds was launched at an elevation angle of 86 degrees and reached an altitude of 746,800 feet compared to the predicted apogee altitude of 755,000 feet.

<mark>A SANDANA A SANDANA SANDANA</mark> SANDANA SANDA

VIII RELATED CONTRACTS

During a previous program conducted under Contract F19628-72-C-0067 from Electronic Systems Division (PPR), Air Force Systems Command, USAF, the development and fabrication of six Ute-Tomahawk sounding rocket vehicles was completed.

IX CONTRIBUTING PERSONNEL

Thickel Chemical Corporation completed the effort required to deliver twenty-two sounding rocket systems by performing tasks in two company divisions and in two plants of one of the divisions.

Tasks and responsible task leaders are listed in Table III. A large number of other participants made significant contributions but are not listed for the sake of brevity.

TABLE III

CONTRIBUTING PERSONNEL - THIOKOL CHEMICAL CORPORATION

Task	Task Leaders	Division/Plant
Program Management	Mr. R. G. Moore Mr. G. C. Alford	Wasatch/Astro-Met Wasatch/Astro-Met
Fabricate Ute/Paiute Motors and Static Test	Nr. D. M. George	Wasatch/Wasatch
Fabricate Tomahawk Motors	Mr. J. Mallick	Elkton/Elkton
Fabricate Flight Hardware	Mr. J. D. Lashbrook	Wasatch/Astro-Met
Computational and Analytical Services	Mr. P. W. Hoekstra	Wasatch/Astro-Met

X PROGRAM RESULTS AND RECOMMENDATIONS

Program objectives for fabrication and delivery of twenty-two sounding rocket systems have been successfully completed. Pour static tests of Paiute motors and a flight test of the Paiute-Tomahawk vehicle were completed with near nominal performance. Analyses and computations were compared to test results and indicate the performance parameters for the Ute-Tomahawk and Paiute-Tomahawk vehicles are well understood.

Ute/Paiute-Tomahawk sounding rocket systems provide proven transportation to carry scientific payloads for investigation of the upper atmosphere. In addition to the competitive cost of these systems, they offer advantages including: a wide range of payload-weight/apogee-altitude performance, capability for operations over a wide range of temperatures and in a variety of environments, complete interchangeability of flight hardware, and relative ease in field handling, assembly, and launch.